






X2-MKP (金属化聚丙烯膜抗干扰电容器)

Metallized Polypropylene Film Capacitor, Class X2



X2-MKP are non-inductively wound with metallized polypropylene film as dielectric/electrode with copper-clad steel leads and encapsulated in a plastic case sealed with epoxy resin



SPECIFICATIONS

Rated voltage: 280VAC

Capacitance range: 0.0022-4.7UF

Capacitance tolerance: $\pm 10\%$ (k), $\pm 20\%$ (M)

Operating temperature: 40/100/21

Voltage proof: 4.3UR(5s)

Dissipation Factor: $\leq 0.3\%$ (20°C, 10kHz)

FEATURES

- 1.Box type provides the identical outer appearance
- 2.Very low loss at high frequency,suitable for high current
- 3.High insulation resistance,long life due to self-healing effect
- 4.Withstanding 2.5kV impuls voltage ,class X2
- 5.As an across-the-line type noise suppression capacitor,and suitable for AC purpose



X2-MKP

Part Number	Rated Cap.	250/280VAC					Part Number	Rated Cap.	250/280VAC					Part Number	Rated Cap.	250/280VAC				
		W	H	T	P	d			W	H	T	P	d			W	H	T	P	d
		±0.5	±0.5	±0.5	±1.0	±0.05			±0.5	±0.5	±0.5	±1.0	±0.05			±0.5	±0.5	±0.5	±1.0	±0.05
X2222□28L10	2200pF	13,0	9,0	4,0	10,0	0,6	X2104□28L10	0.10uF	13,0	12,0	6,0	10,0	0,6	X2684□28L15	0.68uF	18,0	21,0	12,0	15,0	0,8
X2332□28L10	3300pF	13,0	11,0	5,0	10,0	0,6	X2104□28L15	0.10uF	18,0	11,0	5,0	15,0	0,6	X2684□28L22	0.68uF	26,5	19,0	10,0	22,5	0,8
X2472□28L10	4700pF	13,0	11,0	5,0	10,0	0,6	X2104□28L15	0.10uF	18,0	12,0	6,0	15,0	0,8	X2684□28L22	0.68uF	26,5	21,5	12,0	22,5	0,8
X2562□28L10	5600pF	13,0	11,0	5,0	10,0	0,6	X2104□28L15	0.10uF	18,0	13,0	6,3	15,0	0,8	X2684□28L27	0.68uF	31,5	19,5	11,0	27,5	0,8
X2682□28L10	6800pF	13,0	11,0	5,0	10,0	0,6	X2154□28L10	0.15uF	18,0	12,0	6,0	10,0	0,6	X2754□28L22	0.75uF	26,5	21,5	12,0	22,5	0,8
X2103□28L10	8200pF	13,0	11,0	5,0	10,0	0,6	X2154□28L15	0.15uF	18,0	13,5	7,5	15,0	0,8	X2754□28L27	0.75uF	31,5	19,5	11,0	27,5	0,8
X2153□28L10	0.010uF	13,0	11,0	5,0	10,0	0,6	X2154□28L22	0.15uF	26,5	15,0	6,0	22,5	0,8	X2824□28L22	0.82uF	26,5	21,5	12,0	22,5	0,8
X2223□28L10	0.015uF	13,0	11,0	5,0	10,0	0,6	X2224□28L15	0.22uF	18,0	13,0	6,3	15,0	0,8	X2824□28L27	0.82uF	31,5	19,5	11,0	27,5	0,8
X2223□28L15	0.022uF	13,0	11,0	5,0	10,0	0,6	X2224□28L15	0.22uF	18,0	14,5	8,5	15,0	0,8	X2824□28L27	0.82uF	31,5	21,6	13,0	27,5	0,8
X2333□28L10	0.022uF	18,0	11,0	5,0	15,0	0,6	X2224□28L22	0.22uF	26,5	16,5	7,0	22,5	0,8	X2105□28L22	1.00uF	26,5	21,5	12,0	22,5	0,8
X2333□28L15	0.033uF	13,0	11,0	5,0	10,0	0,6	X2334□28L15	0.33uF	18,0	14,5	8,5	22,5	0,8	X2105□28L27	1.00uF	31,5	19,5	11,0	27,5	0,8
X2473□28L10	0.033uF	18,0	11,0	5,0	15,0	0,6	X2334□28L15	0.33uF	18,0	16,0	10,0	15,0	0,8	X2105□28L27	1.00uF	31,5	21,6	13,0	27,5	0,8
X2473□28L10	0.047uF	13,0	11,0	5,0	10,0	0,6	X2334□28L22	0.33uF	26,5	17,0	8,5	22,5	0,8	X2155□28L27	1.5uF	32,0	26,0	18,0	27,5	0,8
X2473□28L15	0.047uF	18,0	11,0	5,0	15,0	0,6	X2394□28L22	0.39uF	26,5	17,0	8,5	22,5	0,8	X2205□28L27	2.0uF	32,0	26,0	18,0	27,5	0,8
X2563□28L10	0.056uF	13,0	12,0	6,0	10,0	0,6	X2474□28L15	0.47uF	18,0	16,0	11,0	15,0	0,8	X2205□28L27	2.0uF	32,0	31,0	22,0	27,5	0,8
X2563□28L15	0.056uF	18,0	11,0	5,0	15,0	0,6	X2474□28L22	0.47uF	26,5	19,0	10,0	22,5	0,8	X2225□28L27	2.2uF	32,0	31,0	22,0	27,5	0,8
X2683□28L10	0.068uF	13,0	12,0	6,0	10,0	0,6	X2474□28L27	0.47uF	31,5	19,5	11,0	27,5	0,8	X2225□28L31	2.2uF	38,0	28,0	18,0	31,0	1,0
X2683□28L15	0.068uF	18,0	11,0	5,0	15,0	0,6	X2564□28L15	0.56uF	18,0	21,0	12,0	15,0	0,8	X2305□28L31	3.0uF	38,0	30,0	20,0	31,0	1,0
X2823□28L10	0.082uF	13,0	12,0	6,0	10,0	0,6	X2564□28L22	0.56uF	26,5	19,0	10,0	22,5	0,8	X2335□28L31	3.3uF	38,0	30,0	20,0	31,0	1,0
X2823□28L15	0.082uF	18,0	11,0	5,0	15,0	0,6	X2564□28L2	0.56uF	31,5	19,5	11,0	27,5	0,8	X2475□28L37	4.7uF	41,5	32,0	19,0	37,5	1,0

Unit:mm

<http://www.stcapacitors.com>